



SAFETY DATA SHEET
LUMBERJACK 550 PARQUET ADHESIVE

Page 1
Issued: 28/04/2008
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: LUMBERJACK 550 PARQUET ADHESIVE

Product code: LJ550

Use of substance / preparation: Adhesive for parquet flooring

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024

2. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: TRIMETHOXYVINYL-SILANE 1-10%

CAS: 2768-02-7

[-] R10; [Xn] R20

- BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL)SEBACATE <1%

EINECS: 255-437-1 CAS: 041556-26-7

[N] R50/53; [Sens.] R43

- METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE <1%

EINECS: 280-060-4 CAS: 082919-37-7

[Sens.] R43; [N] R50/53

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

[cont...]

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Allow to solidify and remove by mechanical means.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area.

Storage conditions: Store in cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Paste

Colour: Yellow-green

Odour: Barely perceptible odour

Solubility in water: Not miscible

Viscosity: Highly viscous

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Persistence and degradability: Not biodegradable.

SAFETY DATA SHEET
LUMBERJACK 550 PARQUET ADHESIVE

Bioaccumulative potential: No bioaccumulation potential.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Precautionary phrases: Contains 3-(2-aminoethylamino)propyl trimethoxysilane, bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate, methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R10: Flammable.
R20: Harmful by inhalation.
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R43: May cause sensitisation by skin contact.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.