

## EVERBUILD OIL AWAY



Colour	Product Code	Pack Size	Box Qty
PALE GREEN	OIL1	1Ltr	12

### Product Description

Everbuild Oil Away is the quick and easy solution for removing oil, petrol, diesel and grease stains from driveways and garage floors. Oil Away works on most common surface types including concrete, stone, tarmac, most common paving materials and BBQ areas. Oil away can also be used as a general cleaner to revive the look of pathways and patio areas.

### Benefits

- Ready to use, no diluting required.
- Available in a handy ready to use spray.
- Water clean up.
- 

### Areas for Use

- Removing oil stains from driveways including concrete, stone, tarmac, block paving etc.
- As a general cleaner for paths, patios and driveways.

### Limitations

- Always test a small inconspicuous area prior to full application
- Do not leave on Tarmac for longer than 5 minutes. As quality/condition of Tarmac can vary significantly, always test a small area prior to full application.
- Do not allow Oil Away to dry on the surface.
- Do not apply to hot surfaces or in strong direct sunlight.
- If Oil Away comes into contact with plants or lawn edges, rinse thoroughly with clean water.
- It is the user's responsibility to determine suitability for use. If in doubt contact Technical Services for advice.

### Surface Preparation

Remove any surface debris using a stiff brush. Large deposits of moss/algae should be first treated with Everbuild Moss Away prior to application of Oil Away.

### Application

#### Stain Removal

Oil Away is supplied ready to use and does not require diluting. Spray Oil Away directly onto the stain, work in well with a stiff bristled brush and leave for 5 minutes. Do not allow Oil Away to dry on the surface. Wash down the area with clean fresh water whilst scrubbing with a stiff brush. Further

applications may be required depending on level of soiling. Should this be necessary, repeat procedure until stains are removed.

General Cleaning of Paths Patios etc.

Dampen surface to be treated with water. Apply Oil Away liberally over the area and work in well with a stiff brush. Wash down the area with clean fresh water whilst brushing.

**Specific Data**

<b>Appearance</b>	Thin green/yellow liquid
<b>Specific Gravity @ 20°C</b>	1.02g/cm <sup>3</sup>
<b>pH</b>	7.0-8.0
<b>Odour</b>	Slight.
<b>Coverage</b>	Approx. 5-8m <sup>2</sup> per litre depending on porosity of substrate.

**Health & Safety**

Consult MSDS for full list of hazards.

**Storage**

KEEP AWAY FROM CHILDREN. Store away from alkaline products and bleach at moderate temps.

**Shelf Life**

12 months from date of manufacture.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*